



Type	MK	D	d	d1	L	l1	l2	d2	SW	Drehzahl max. [1/min]	Werkstückgewicht max. [kg]	Rundlaufabweichung max. [mm]	Passende Einsätze [E]	Abdrückgewinde [G]
Type	MK	D	d	d1	L	l1	l2	d2	SW	Rotational frequency max. [1/min]	Workpiece weight max. [kg]	Concentricity run-out max. [mm]	Interchangeable inserts [E]	Draw-off thread [G]
935	3	52	25	23,83	73	10	56	12	19	12000	250	0,005	E923	M 54 x 1.5
945	4	60	28	31,27	80	10	63	14	22	10000	400	0,005	E933	M 62 x 1.5
955	5	72	35	44,40	103	14	82	18	30	8000	800	0,005	E943	M 74 x 1.5
965	6	83	44	63,35	110	15	88	24	36	5000	1200	0,005	E953	M 85 x 1.5

- Auswechselbare Einsätze siehe Seite 38-41
 - Max. Axialdruck entsprechend Reihe 805

- For interchangeable inserts, see pages 38-41
 - Max thrust load according to Series 805

Produkteigenschaften

- ▶ Gleiche Ausführung wie Reihe 805, jedoch mit auswechselbaren Körnereinsätzen für maximale Flexibilität
- ▶ Auswechseln der Einsätze durch gegenseitiges Verdrehen mit zwei Gabelschlüsseln an den Schlüssel­flächen von Achse und Einsatz
- ▶ Abdrückmutter nach CONZELLA-Werksnorm
- ▶ Für hohe Drehzahlen und hohe Axialkräfte
- ▶ Hohe Rundlaufgenauigkeit durch High-End Lagerung
- ▶ Komplettes Werkzeug gehärtet und geschliffen
- ▶ Wartungsfreie Dauerschmierung
- ▶ Wellendichtring verhindert Eindringen von Schmutz und Kühlflüssigkeit
- ▶ Mit Zusatzdichtung auch für Schleifanwendungen geeignet

Product features

- ▶ Same configuration as 805-series but with interchangeable inserts for maximum flexibility
- ▶ Replacement of inserts by the opposing action of two open-end wrenches on the flats of the abor and insert
- ▶ Draw-off nut according to Conzella factory standard
- ▶ For high rotary speeds and axial load
- ▶ High concentricity run-out accuracy through high-end bearings
- ▶ Complete tool hardened and ground
- ▶ Maintenance-free permanent lubrication
- ▶ Rotary shaft seal prevents penetration of dirt and coolant
- ▶ With additional seal, also suitable for grinding applications